

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

FLO.LAM.OAK

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

FLORIAN LEGNO S.P.A.

Via Castellana 48/A

IT-31039 Riese Pio X (TV)

and produced in the manufacturing plant

Flo drvo d.o.o.

Ulica Tečine 4

HR-32276 Babina Greda

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-25/0265, issued on 29.04.2025

and

EAD 130320-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0881

Date of first issue: 14.05.2025

Date of issuance: 14.05.2025

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforchung.at.



Dipl.-Ing. (BA) Eugen Spitaler

Authorised signatory



PD Gerhard Grüll

Head of the Certification Body

Addendum to certificate 1359-CPR-0881

Date of issuance: 14.05.2025

Scope of certification:

FLO.LAM.OAK

| | |
|------------------------------------|--|
| Wood species / strength classes: | QCXE – European Oak: characteristic values according to ETA-25/0265, table 5 |
| Strength class of the laminations: | LS 10+ according to ETA-25/0265, table 2 |
| Service classes: | 1, 2, 3 |
| Adhesive | |
| - Finger joints | Type I: MUF according to EN 301 |
| - Surface bonding: | Type I: MUF according to EN 301 |
| Reaction to fire: | No performance determined |
| Formaldehyde class: | No performance determined |
| Natural durability class: | according to EN 350 |