

FLO.2 Layer - WALNUT

TRADE NAME OF THE PRODUCT:	FLO.2 Layer
PRODUCT REFERENCE STANDARD:	UNI EN 13489:2023 Multi-layer parquet elements for internal use as flooring.
WOOD SPECIES USED:	Surface layer: <i>Juglans nigra</i> or <i>Juglans regia</i> .
PRODUCT CONSTITUTIVE ELEMENTS:	First layer: walnut saw veneer Second layer: birch plywood.
PRODUCT FINISH:	micro-bevel on all sides of the elements with a brushed or non-brushed walking surface, in any case painted with a water-based product pigmented in line with UV drying.
TYPE OF LAYING:	glued or floating: following the installation manual instructions scrupulously
SIZE OF THE PRODUCT:	
Overall thickness of the product:	15 mm $\pm$ 0.5 - top layer 4 mm (top layer 3 and 6 mm on request. Thickness in reference to what is indicated in the order confirmation).
Width:	192 mm (152 mm, 142 mm or under measures, based on availability and in reference to what is indicated in the order confirmation)
Length:	1175 - 1850 - 2150 - 2350 mm or under measures, based on availability and in reference to what is indicated in the order confirmation

TEST	REFERENCE	VALUE
CE MARKING	EN14342:2013	CE
FORMALDEHYDE EMISSION	EN 717-1:2004	E1 - $\leq 0,062$ mg/m ³ Reg (UE) 2023/1464
PENTACHLOROPHENOL	CEN/TR 14823:2003	≤ 5 ppm
RESISTANCE TO FIRE		Dfl-s1 Minimum mean density - 500 (Kg/mc) Minimum overall thickness 10 mm Without airgap underneath
THERMAL CONDUCTIVITY	UNI EN 14342:2013	0,16 W/mK
DURABILITY	EN 335:2007	Class 1
LOCKING SYSTEM	EN 13489:2023	Tongue and groove

