

FLO.3 Layer - OAK

TRADE NAME OF THE PRODUCT:	FLO.3 Layer
PRODUCT REFERENCE STANDARD:	UNI EN 13489:2023 Multi-layer parquet elements for internal use as flooring.
WOOD SPECIES USED:	Surface layer: Quercus spp.
PRODUCT CONSTITUTIVE ELEMENTS:	First layer: oak saw veneer Second layer: birch plywood Under layer: oak saw veneer
PRODUCT FINISH:	micro-bevel on all sides of the elements with a brushed or non-brushed walking surface, in any case painted with a water-based product pigmented in line with UV drying. Available in several colours.
TYPE OF LAYING:	glued or floating: following the installation manual instructions scrupulously
SIZE OF THE PRODUCT:	
Overall thickness of the product:	15 mm $\pm$ 0.5 - top layer 4 mm.
Width:	192 mm (242 or 152 mm or under measures, based on availability and in reference to what is indicated in the order confirmation)
Length:	1175 - 1850 - 2150 - 2350 mm or under measures, based on availability and in reference to what is indicated in the order confirmation

TEST	REFERENCE	VALUE
CE MARKING	EN14342:2013	CE
FORMALDEHYDE EMISSION:	EN 717-1:2004	E1
PENTACHLOROPHENOL	CEN/TR 14823:2003	≤ 5 ppm
RESISTANCE TO FIRE	UNI EN 13501-1:2018	Cfl-s1
THERMAL CONDUCTIVITY	UNI EN 14342:2013	0,17 W/mK
DURABILITY	EN 335:2007	Class 1
DENSITY	/	750 $\pm$ 50 kg/m ³
LOCKING SYSTEM	EN 13489:2023	Tongue and groove

