

# FLO.LIGHT

|                                   |                                                                                                                                                                          |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TRADE NAME OF THE PRODUCT:        | FLO.LIGHT                                                                                                                                                                |
| PRODUCT REFERENCE STANDARD:       | UNI EN 13489:2023<br>Multi-layer parquet elements for internal use as flooring.                                                                                          |
| WOOD SPECIES USED:                | Surface layer: Quercus spp. - Body: Abies alba/Picea abies.                                                                                                              |
| PRODUCT CONSTITUTIVE ELEMENTS:    | First layer: oak saw veneer<br>Second layer: perpendicular fir elements<br>Third layer: fir peeled veneer                                                                |
| PRODUCT FINISH:                   | micro-bevel on all sides of the elements with a brushed or non-brushed walking surface, in any case painted with a water-based product pigmented in line with UV drying. |
| TYPE OF LAYING:                   | glued or floating: following the installation manual instructions scrupulously                                                                                           |
| SIZE OF THE PRODUCT:              |                                                                                                                                                                          |
| Overall thickness of the product: | 12,5 mm $\pm$ 0.5 - top layer 2.5 mm (top layer 3 and 4 mm on request.<br>Thickness in reference to what is indicated in the order confirmation).                        |
| Width:                            | 192 mm (152 mm or under measures, based on availability and in reference to what is indicated in the order confirmation)                                                 |
| Length:                           | 1175 - 1850 - 2150 - 2350 mm or under measures, based on availability and in reference to what is indicated in the order confirmation                                    |

| TEST                   | REFERENCE           | VALUE                                                  |
|------------------------|---------------------|--------------------------------------------------------|
| CE MARKING             | EN14342:2013        | CE                                                     |
| FORMALDEHYDE EMISSION: | EN 717-1:2004       | E1 - $\leq 0,062$ mg/m <sup>3</sup> Reg (UE) 2023/1464 |
| PENTACHLOROPHENOL      | CEN/TR 14823:2003   | $\leq 5$ ppm                                           |
| RESISTANCE TO FIRE     | UNI EN 13501-1:2018 | Dfl -s1                                                |
| THERMAL CONDUCTIVITY   | UNI EN 14342:2013   | 0,13 W/mK                                              |
| DURABILITY             | EN 335:2007         | Class 1                                                |
| DENSITY                | /                   | 500 $\pm$ 50 kg/m <sup>3</sup>                         |
| LOCKING SYSTEM         | EN 13489:2023       | Tongue and groove                                      |

